



Lightweight, easy to operate, portable test set

The PSD60-1AF is designed to calibrate and troubleshoot any AC capacitive fuel, oil or LOX quantity system. This venerable test set is utilized extensively by rotary and fixed-wing military aircraft operators around the world. The PSD60-1AF will:

- Measure the capacitance of any AC capacitive fuel, oil or LOX quantity transmitter, or sets of transmitters connected in parallel.
- Simulate either one or two capacitors simultaneously to calibrate any AC capacitive liquid quantity gauging system.
- Measure the insulation resistance in meg-ohms of capacitive liquid quantity transmitters (probes) and/or aircraft wiring.

### FEATURES

- Solid-state circuits and LCD backlit display for low power consumption and high reliability
- Battery-powered for complete portability and ease of maintenance
- Lightweight aluminum case has hinged compartment in lid for test lead storage
- Small size permits testing in restricted spaces
- Push-button “extended range” switch permits readings up to 9,999 pf or 10,000 MΩ - over-range indication on LCD
- Tested and approved for use in any function with fuel in tanks; battery power eliminates need for voltage (safety) checks

## SPECIFICATIONS

### MEASUREMENT RANGE

Capacitance	0.1 to 1,999 pf (or 1 to 19,999 pf in “extended range”)
Resistance	0.1 to 19,999 MΩ (auto-ranging)

### CAPACITANCE SIMULATION RANGE

Tank Unit	15 pf to 8,000 pf
Compensator	15 pf to 1,000 pf

### ACCURACY OF MEASUREMENT OR SIMULATION

±.10% of reading or .2 pf to 10,000 pf, whichever is greater, from 0 to +50° C  
 ±.15% of reading or .3 pf to 10,000 pf, whichever is greater, from -25 to +55° C  
 ±10% of reading to 10,000 MΩ in insulation resistance mode, from 0 to +50° C  
 ±15% of reading to 10,000 MΩ in insulation resistance mode, from -20 to +55° C

### TEMPERATURE RANGE

Operating	-20° C to +55° C
Storage	-51° C to +71° C

## CALIBRATION & WARRANTY

---

Annual calibration  
Two year warranty

## PHYSICAL CHARACTERISTICS

---

Weight	12 lbs (5.44 kg)
Width	12.0 in (30.5 cm)
Height	6.0 in (15.2 cm)
Depth	9.0 in (22.9 cm)



*Aircraft fuel interfaces available for purchase*

## VERSIONS, OPTIONS AND ACCESSORIES

When ordering, please include the order number listed below.

Order Number	Versions
699	PSD60-1AF AC Fuel Capacitance Test Set

Aircraft specific interface cables are required and must be purchased separately. Contact Cobham AvComm for your application.

### Standard Accessories

57306	Cable, Hi-Z BNC to two-clip (55-0605-13)
57307	Cable, Lo-Z polarized BNC to alligator clip (55-0605-14)
57308	Cable, Hi-Z BNC to BNC (55-0605-15)
57309	Cable, polarized BNC to standard BNC (55-0605-16)
58345	Cable, ground strap (55-7002-00)

### Extended Warranty

84388	Extended standard warranty 36 months with scheduled calibration
84389	Extended standard warranty 60 months with scheduled calibration

# COBHAM

For further information please contact:

**Cobham AvComm**  
10200 West York Street  
Wichita, KS 67215-8935 [USA]  
Phone: (316) 522-4981  
Fax: (316) 524-2623  
AvComm.TechSales@aeroflex.com

or contact your Cobham AvComm sales office