

VIAVI

IFF-45TS

MK XIIA and TACAN Bench Test Set

A leading edge RF signal generator/receiver designed for engineering manufacturing and return-to-service applications

The IFF-45TS test set provides RF signal generation and parametric measurement of MK XIIA and TACAN equipment. Replies and interrogations can be individually configured to support MK XIIA testing requirements. ADS-B Out testing monitors ADS-B, TIS-B, ADS-R and acquisition squitters. The IFF-45TS emulates either a TACAN ground transponder or a TACAN airborne interrogator, providing six TACAN test modes:

- Ground to Air
- Inverse Air to Air
- Inverse Ground to Air
- Beacon Ground to Air
- Air to Air
- Beacon Air to Air

For a fully configurable automated test solution using the IFF-45TS as the RF source, see the VIAVI Solutions IFF-7300S Series Automated Test System.



Features

- MK XIIA AIMS certified for Level 1 and Level 2
- Mode 5 testing without actual cryptographic applique and keys using integral mode 5 emulator
- Supports DoD AIMS 04-900A Option A – KIV-78 & QRTK6 NG (with Airbus DS QRTK6 NG adapter) and Option B – KIV-77 & SIT-2010 crypto appliqués (part number 72438 only)
- Dual I/O for diversity testing of transponders or SUM/DIFFERENCE on interrogators
- Separate connections for direct or over-the-air testing
- Software defined radio design allows waveform flexibility and future growth potential
- Dual signal generator design allows coordinated signal production for interference and echo testing
- Remote interfaces consist of RS-232, Ethernet and GPIB
- Graphical User Interface (GUI) allows easy access to test features
- Test ranges of up to 3 km with appropriate antennas

Applications

- Engineering – Development and qualification testing for MK XIIA, ADS-B Beacon, and TACAN equipment
- Manufacturing – factory calibration and verification testing
- Depot/Service – Level 1 and 2 return-to-service testing
- Support for DO-260B, AIMS 03-1000B, Amendment 1 and DO-181E certification testing
- Over-the-air platform testing of MK XIIA equipment including Mode 5, ADS-B beacons and TACAN interrogators
- Industry-wide use for development and end item testing of transponders and interrogators

Ordering Information

Versions and Options

Order Number	Description
72438	IFF-45TS Transponder Modes 1,2,3/A,4 (Internal Crypto),C,S (Mode 5 capable)
72439	IFF-45TS-A Transponder Modes 1,2,3/A,4 (Internal Crypto),C,S
140612	SERD 65A08, Kit, IFF-45TS Test Set
83404	45TSOPT1 IFF Transponder Mode 5 (for use with Order Number 72438 only)
83405	45TSOPT2 Interrogator Modes 1,2,3/A,C,S,4
83406	45TSOPT3 IFF Interrogator Mode 5 (for use with Order Number 72438 only, requires option 2 (83405))
83407	45TSOPT4 DME/TACAN
91684	45TSOPT5 ADS-B Out
140608	45TSOPT10 ADS-B Out Integrity Test App
112120	Kit, ADS-B Out (fielded units), IFF-45TS
112364	Kit, ADS-B Out (fielded units), IFF-45TS-A

NSN Information

6625-01-617-2567	IFF-45TS w/options 1, 2, 3, 6, 8, 9
6625-01-611-6485	IFF-45TS w/options 2 and 8

Standard Accessories

92053	PC Windows-based GUI (IFF45TS)
92054	Operation Manual (CD) (IFF45TS)
6138	Getting Started Manual (IFF45TS)
92053	PC Windows-based GUI (IFF45TS-A)
92054	Operation Manual (CD) (IFF45TS-A)
6141	Getting Started Manual (IFF45TS-A)
62302* or 62315**	AC power cord, *110V or **220V
30050	Serial data cable, 9 pin D, 1.5 meters

Extended Warranty (2 year standard)

84363	36 months with scheduled calibration
84364	60 months with scheduled calibration

Export Control and Warning

VIAVI Solution's military products are controlled for export under the International Traffic in Arms Regulations (ITAR). A license from the U.S. Department of State is required prior to the export of this product from the United States. This product may not be sold or proposed or offered for sale to certain countries including: Belarus, Burma, China, Cuba, Haiti, Iran, Liberia, Libya, North Korea, Somalia, Syria, Sudan, and Vietnam. See ITAR 126.1 for complete information.



Contact Us +1 316 522 4981
AvComm.Sales@viavisolutions.com

To reach the VIAVI office nearest you, visit
viavisolutions.com/contact.

© 2020 VIAVI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
IFF-45TS-br-avi-nse-ae
30187399 902 0320

viavisolutions.com

Optional Accessories

88631	45TSOPT6 KIV 77 adapter (Opt B)
89879	45TSOPT8 KIT/KIR-1A/C adapter
86075	45TSOPT9 KIV 78/KIV 6 adapter (Opt A)
63975	Controller w/ touch-screen monitor, w/ Mode 5 GUI
140416	Controller w/ touch-screen monitor, w/ Mode 4 GUI
112349	UC-584 coupler kit, dual antenna
112350	UC-584 coupler kit, single antenna
138553	Kit, Laptop with IFF-45TS Mode 4 GUI
138552	Kit, Laptop with IFF-45TS Mode 5 GUI
138512	Transit Case, IFF-45TS
93023**	IFF-45TS Maintenance Manual
89345**	IFF-45TS-A Maintenance Manual
112684	Antenna

**Includes remote program GUI

Physical Characteristics

Size: Test Set Only	4"H x 17.75"W x 21"D (10 cm x 45 cm x 53 cm)
Weight	24 lbs. (10 kg)

Environmental

Operational Temp.	-10° to +55°C (+14° to +131° F)
Storage Temp.	-10° to +55°C (+14° to +131° F)

Test Set Certifications

UL
CE
DoD AIMS MK XIIA Level 1 and Level 2
For complete certification list see IFF-45TS Specification Sheet